

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
9 February 2006 (09.02.2006)

PCT

(10) International Publication Number
WO 2006/013868 A1

(51) International Patent Classification:

F02D 19/08 (2006.01) **F02M 25/00** (2006.01)
F02M 21/02 (2006.01) **F02D 41/00** (2006.01)

(74) Agents: **TAKAHASHI, Hideki** et al.; TAKADA, TAKAHASHI & PARTNERS, 5th F., Intec 88 Bldg., 20, Arakicho, Shinjuku-ku, Tokyo, 1600007 (JP).

(21) International Application Number:

PCT/JP2005/014147

(22) International Filing Date: 27 July 2005 (27.07.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

2004-227812 4 August 2004 (04.08.2004) JP

(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **ITO, Yasushi** [JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: CONTROL SYSTEM FOR HYDROGEN ADDITION INTERNAL COMBUSTION ENGINE



(57) Abstract: Disclosed is a control system for a hydrogen addition internal combustion engine that uses hydrocarbon fuel and hydrogen gas as combustion fuel. The control system includes a canister 52 for adsorbing fuel vapor generated in a tank 34 for storing the hydrocarbon fuel; a purge VSV 66 for purging the fuel vapor into an intake port 18 of the hydrogen addition internal combustion engine in a predefined situation; hydrogen addition ratio setup means for setting the ratio of hydrogen gas addition to the hydrocarbon fuel; and hydrogen gas addition ratio adjustment means for increasing the ratio of hydrogen gas addition when the fuel vapor is purged into the intake port 18.



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.